

6.5Kw/hr Average Performance Tracking

System Size in Watts											
Head (m)	175	260	350	435	525	610	700	1050	1400	2100	2800
5	27.0	30.0	47.0	98.0	104.0	107.0	112.0	116.0	117.0	118.0	120.0
10	22.0	28.0	43.0	70.0	86.0	93.0	99.0	111.0	115.0	116.0	117.0
15	17.0	25.0	37.0	53.0	63.0	67.0	80.0	103.0	112.0	114.0	115.0
20	14.0	21.0	30.0	41.0	52.0	58.0	63.0	93.0	107.0	112.0	113.0
25	12.0	17.0	24.0	33.0	42.0	48.0	53.0	79.0	101.0	108.0	111.0
30	9.0	15.0	19.0	23.0	30.0	34.0	44.0	65.0	94.0	104.0	108.0
35	8.0	12.0	18.0	21.0	25.0	29.0	37.0	58.0	85.0	98.0	105.0
40	7.0	11.0	15.0	19.0	24.0	26.0	31.0	51.0	68.0	73.0	75.0
45	6.0	10.0	13.0	18.0	22.0	24.0	26.0	44.0	64.0	70.0	74.0
50	5.0	9.0	12.0	16.0	20.0	23.0	25.0	39.0	60.0	68.0	72.0
55	5.0	8.0	11.0	15.0	18.0	21.0	23.0	36.0	55.0	65.0	70.0
60		7.0	11.0	13.0	17.0	19.0	22.0	33.0	43.0	46.0	48.0
65		6.0	10.0	12.0	16.0	18.0	19.0	30.0	42.0	44.0	47.0
70		6.0	9.0	11.0	15.0	17.0	18.0	26.0	40.0	43.0	46.0
75		5.0	8.0	10.0	13.0	15.0	16.0	25.0	38.0	42.0	45.0
80		5.0	7.0	9.0	12.0	14.0	15.0	24.0	36.0	41.0	44.0
85				8.0	11.0	13.0	14.0	23.0	35.0	40.0	44.0
90				7.0	10.0	12.0	13.0	22.0	33.0	39.0	43.0
95				7.0	9.0	11.0	12.0	20.0	25.0	27.0	28.0
100				6.0	8.0	10.0	11.0	18.0	25.0	27.0	28.0
105				6.0	7.0	9.0	10.0	17.0	24.0	26.0	27.0
110				5.0	6.0	8.0	9.0	15.0	23.0	25.0	27.0
115				5.0	5.0	7.0	8.0	14.0	22.0	24.0	26.0
120				4.0	5.0	7.0	8.0	12.0	21.0	24.0	25.0
125							7.0	11.0	19.0	23.0	25.0
130							7.0	10.0	17.0	23.0	24.0
135							6.0	10.0	16.0	21.0	23.0
140							6.0	9.0	15.0	20.0	22.0
145							5.0	9.0	14.0	19.0	22.0
150							4.0	8.0	13.0	18.0	21.0

 1000 Series  
Motor & Controller

 2000 Series  
Motor & Controller

 3000 Series  
Motor & Controller

Figures indicate average daily Flow x 1000 litres/m<sup>3</sup>

\* Use Cass to accurately estimate average daily flow for your region